

ES-200

Fully Automatic Chemistry Analyzer

Technical specifications

General information

Machine type	Random access, open reagent & locked reagent (optional)
Test speed	Constant 200 tests/hour (Mono reagent or double reagent)
Test principle	Colorimetric method, turbidimetry
Test method	1 point end, 2 point end, Fixed-Time, Kinetics
Calibration type	Linear & nonlinear

Sample unit

Sample tray	40 sample positions
Sample tube	Micro cup & test tube & blood collection tube can be used. (Φ 12 -13)mm * (25 – 100)mm
Sample volume	2-30 μ L, step by 0.1 μ L
Sample probe	Liquid surface detection, timely tracking for liquid volume. Collision avoidance
Sample barcode	Sample barcode reader (optional)

Reagent unit

Reagent tray	80 reagent positions (40 for R1 & 40 for R2), Non-stop cooling system with peltier pad inside, 24 hours 2 $^{\circ}$ C -14 $^{\circ}$ C, open system, could accept any reagent.
Reagent volume	20-300 μ L, step by 1 μ L
Reagent needle	Liquid surface detection, timely tracking for liquid volume. Collision avoidance.
Reagent barcode	Reagent barcode reader (optional)

Reaction unit

Reaction tray	44 reaction cuvettes, new amorphous optical plastics reaction cups, perfect transmittance.
Reaction volume	150 μ L-330 μ L
Reaction time	10 minutes
Temperature	Peltier pad incubation system, reaction temperature (37 $^{\circ}$ C \pm 0.1 $^{\circ}$ C)

Mixing system

Mixer	paddle-type mixing, effective reducing of carry-over
-------	--

Optical system

Light source	Halogen lamp
Wavelength	340nm; 405nm; 450nm; 505nm; 546nm; 578nm; 630nm; 700nm(4 more options)
Absorbance range	0-4.0 Abs
Resolution	0.0001 Abs

Operating system

Operation system	Windows XP, Windows 7, Windows 8, Windows 10
Data processing	Automatic calibration, test combination, effective time management of reagents, serum index, whole process detection, linear expansion of enzyme, blank deduction, dirty cuvette memory, cross infection prevention, patient information memory and association input, automatic report audit, data fuzzy query, report statistics and printing, reference range grading, alarm information classification, user operation privilege classification management.
Report printing	6 formats optional, support custom pattern
interface	TCP/IP network interface

Working conditions

Power supply	AC 110/220V \pm 10%, 50/60 Hz, 650W
Water consumption	8L/hour(maximum)
Dimension	780mm * 565mm * 1120mm(L*W*H)
Weight	140kg



ΛΕΩΦ. ΜΑΡΑΘΩΝΟΣ 19
ΓΕΡΑΚΑΣ 15344
ΤΗΛ: 2168002528

BIOELAB



WeChat Subscrip

E-LAB BIOLOGICAL SCIENCE & TECHNOLOGY CO., LTD.

Address: No. 108, Ganjiabiandong, Yaohua Street, Qixia District,
Nanjing city, Jiangsu Province, China

Tel : 086-025-83269256

Fax : 086-025-83269255

Web : www.bioelab.net

E-mail : Jason.lu@bioelab.net

E-LAB reserves all rights to make any modification of machine without prior notice.

The customer service hot line in 24 hours

400-018-6818

